

identium
Creating identities for all

identag
tags by identium

identraces
Trace your identity

RFID

UHF Integrated Reader

IDTS - UR 88 SL

Datasheet

Identium Tech Solutions

New Delhi

India

Email: tags@identags.com

Ph: (+91) 7827944632 , 9711863861



Identium Tech Solutions

Main Office: 736-2/7, Lower Ground Floor Govindpuri, Kalkaji, New Delhi – 110019

Email: info@identium.in, paras@identium.in

Ph: (+91) 7827944632 , 9718199516

Identium UHF Long Range Reader IDTS - UR88 SL



Introduction:

Identium UHF Long Range Reader IDTS-UR88 SL is a popular integrated reader, Compatible with ISO18000-6C (EPC C1GEN2) and ISO18000-6B.

It is an industry grade product for harsh environment, IP-65 protection case for water-proof, easy to install.

Application:

- Parking management: Long range intelligent parking management and automatic charge without stop the car
- Production line management: Goods identification for production flow
- Auto Access control: Long range access control management for custom, sea port
- Logistics and warehouse management
- People auto registry for important meeting or exhibition

Identium Tech Solutions

Main Office: 736-2/7, Lower Ground Floor Govindpuri, Kalkaji, New Delhi – 110019

Email: info@identium.in, paras@identium.in

Ph: (+91) 7827944632 , 9718199516

Specifications:

Model No.	IDTS – UR88 SL
Frequency range	902-928MHZ(or customized)
Protocol	ISO18000-6B, EPC Class 1 Gen2(18000-6C)
FM mode	FHSS or fixed frequency, set by the software
RF output	30dBm adjustable;50Ω load
Communication interface	LAN,RS232,RS485,Wiegand26/34,IEEE 802.11 (TCP/IP & Wifi Optional)
Power dissipation	average<10W
Application software	Provide with Demonstration Software and SDK
Tag Operation Performance	
Reading distance	0 – 15m equipped with 12dbi antenna(tag dependent)
Air interface	EPC global UHF ISO-18000-6C(EPC G2), ISO-18000-6B
Mechanical and Electrical Performance	
Dimension	255(L)*255(W)*42(H)mm
Power supply	Equipped with power convertor 220V AC input, +9V/3A DC output
Weight	2.0Kg
Humidity	10% to 95%, non-condensing
Protection grade	IEC IP65
Regulatory	Compliant with CE, FCC
Operation temperature	-20 °C to +60 °C

Identium Tech Solutions

Main Office: 736-2/7, Lower Ground Floor Govindpuri, Kalkaji, New Delhi – 110019

Email: info@identium.in, paras@identium.in

Ph: (+91) 7827944632 , 9718199516

Queries/Samples?

Call us : +91 7827944632

+91 9716089324

Write to us: tags@identags.com

info@identraces.com

info@identium.in

RFID: IDentium.in

Race timing: IDentraces.com

tags: IDentags.com



Identium Tech Solutions

Main Office: 736-2/7, Lower Ground Floor Govindpuri, Kalkaji, New Delhi – 110019

Email: info@identium.in, paras@identium.in

Ph: (+91) 7827944632 , 9718199516